Lithium Battery - Golf Cart Series

GP48-80



Features Of LiFePO4 Battery

- · Long cycle life
- · High integration, small size, high energy density
- Intelligent management of product usage status with high security
- Environmental protection
- Capable of 1C fast charging

Application scenarios

- Golf Cart
- Patrol vehicles
- Venue vehicle
- Electric tricycle
- Sightseeing Bus

| Specification | |
|--------------------------|--------------------------------|
| Nominal Voltage | 48V |
| Working Voltage | 37.5-54.75V |
| Nominal Capacity | 82Ah |
| Energy | 3936Wh |
| Self Discharge | ≤3% Per Month |
| IP Grade | IP65 |
| Positive material | Lithium ironphosphate |
| Cell type | Prismatic |
| Combination method | 82Ah,1P15S |
| Weight | ABOUT 45.0KG |
| Dimension LxWxH | L482.6*W353*H263mm |
| Fixed size | L240*W338mm |
| Terminal Type | M8 Terminal Bolts,12±2N·m |
| Shell type | Powder Coated Steel |
| Handle | YES |
| Storage Temp. short term | -20-45°C |
| Storage Temp. long term | 0~35 ℃ |
| Cycle Life | 5000 cycles |
| Heating function | No |
| Cooling type | No |
| Insulation | 20MΩ/1000VDC, @25±5°C,RH50% |
| | |



| Charging | |
|-------------------------|---------------|
| Recom. Charging Current | 40A |
| Upper limit voltage | 54.75V |
| Charging Temp. Range | 0~55 ℃ |

| DisCharging | |
|--------------------------|----------|
| Max Continuous Discharge | 80A |
| Max Discharge current | 240A@30S |
| Lower limit voltage | 37.5V |
| BMS Voltage Recovery | 42V |
| Discharge Temp. Range | -20~55°C |

Function (optional)

(CAN/RS485), Bluetooth, 4G, Screen, Charger

Physical Dimension-mm





